

# Mini Converter Analog to SDI



The ideal solution for converting analog component, s-video, NTSC/PAL composite to SDI video. Audio can be embedded from balanced analog or AES/EBU inputs. Now you can convert analog devices such as Betacam SP, VHS, set top boxes, gaming consoles and HDV cameras to incredible quality SD/HD-SDI video.

**\$195**

## Connections

### SDI Video Outputs

2 x SDI Video Outputs.

### Analog Audio Inputs

2 channels of balanced analog audio.

### Multi Rate Support

Auto detection of SD or HD.

### Analog Video Inputs

NTSC, PAL, S-Video and Component SD/HD input.

### Digital Audio Inputs


2 channels of balanced AES/EBU audio.

### Updates and Configuration

Via USB 2.0 high speed. (480 Mb/s)

### Reclocking

Yes



## Standards

### SD Video Standards

525i59.94 NTSC, 625i50 PAL

### SDI Compliance

SMPTE 259M, SMPTE 292M, SMPTE 296M, ITU-R BT.656 and ITU-R BT.601.

### SDI Video Sampling

4:2:2

### HD Video Standards

720p50, 720p59.94, 720p60  
1080i50, 1080i59.94, 1080i60

### SDI Audio Sampling

Television standard sample rate of 48 kHz and 24 bit.

---

**SDI Color Precision**

4:2:2

**SDI Auto Switching**

Automatically follows format of analog input.

**Analog Color Space**

YUV

**SDI Color Space**

YUV

**Analog Color Precision**

4:2:2

---

**Software****Software Control**

Mac™ and Windows™ software upgrade via USB.

**Internal Software Upgrade**

Via included updater application.

---

**Power Requirements****Power Supply**

+12V universal power supply included with international socket adapters for all countries. Cable tie point.

**Power Consumption**

6.50 Watts

**Operational Voltage Range**

12 - 31V DC

---

**Settings Control**

Mini Switches or USB software.

---

**Operating Systems**Mac 10.15 Catalina,  
Mac 11.1 Big Sur or later.

Windows 10, 64-bit.

---

## Physical Specifications



---

## Environmental Specifications

### Operating temperature

0° to 40° C (32° to 104° F)

### Storage temperature

-20° to 45° C (-4° to 113° F)

### Relative Humidity

0% to 90% non-condensing

---

## What's Included

Mini Converter Analog to SDI

12V AC adapter with international socket adapters for all countries.

---

## Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2022, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller