



JIAD E ENERGY TECHNOLOGY (ZHUHAI) CO., LTD.
HEAD OFFICE

ADD: Jiade Technology Industrial Park, The 7th Dingwan Road, Dingjiawan Industrial Park, Sanzao Town, Jinwan District, Zhuhai, China
Tel: +86-756-8287186, 8287286, 8287386
Fax: +86-756-8287686
P.C.: 519040

BEIJING OFFICE

ADD: Room 204, Unit 3, #2 Block Jin Shang Jia Yuan, #2 Hua Yuan Road, Haidian District, Beijing, China
Tel: +86-10-82029531
Fax: +86-10-82029531
P.C.: 100083

GUANGZHOU OFFICE

ADD: Room 1711, Northern Tower, Yu Dong He Fu, 39# Nong Lin Xia Road, YueXiu District, GuangZhou, China
Tel: +86-20-85629960
Fax: +86-20-85629965
P.C.: 510080

Http: [//www.blbattery.com](http://www.blbattery.com)
E-mail: service@blbattery.com

BEILLEN



We Power, You Film
BEILLEN BATTERY

About Us

Jiade Energy Technology (Zhuhai) Co., Ltd. is a high technology enterprise specialized in design and production of high power battery packs for portable devices. Our products are widely applied in digital products and power unit, such as professional video camera, digital camera, cellular phone and PDA.

Jiade believes in the management concept of 'people oriented, capable team, strict standard and speedy & strict enforcement', as well as the quality policy of 'technology first, guaranteed quality, continual improvement and customer satisfaction'. We have a united and crack management and R&D team, of which all the key members have service experiences for some large companies, such as Motorola. Jiade also posses strong R&D and mass production capability of mold, PCM and charger to guarantee project development and product quality.

'Beillen' is our self-developed registered trademark for professional video camera battery and charger, which has been successfully popularized into the domestic and international market (e.g. Europe and USA) and won good reputation. We have been cooperating well with many famous enterprises, such as SANYO, SAMSUN, LG, TOCAD, REWA, SIGMA-ALDRICH, OLYMPUS, LONGCHEER, SIMCOM, HUAQIN, WINTech, HUAWEI, DEWAV, FOXLINK, FEIXUN, XINWEI, DATANG, HYT, KONKA, HISENSE, SKYWORTH, XINRI and NEWSMY.

Jiade has obtained ISO9001:2008 certificate for good quality control system and ken-witted and capable R&D team. Most of our products have also obtained UN38.3, CE or UL certificate. Moreover, we have successfully applied many patents of utility model, appearance and invention. Jiade has also received the recognition of Hong Kong Jockey Club, TVB and Media Corporation of Singapore Pte Ltd for high-quality product and good customer service.



NEW



see details

P1

Broadcasting Video Camera Battery

- BL-BP/AN95NE BL-BP/AN130NE BL-BP/AN160NE
BL-BP/AN190NE BL-BP/AN230NE
BL-BP/AN95NC BL-BP/AN130NC BL-BP/AN160NC
BL-BP/AN190NC BL-BP/AN230NC



High Load



see details

P3

High Load Battery for Broadcasting Video Camera

- BL-BP/AN93HE BL-BP/AN125HE BL-BP/AN155HE
BL-BP/AN185HE BL-BP/AN210HE BL-BP/AN255HE
BL-BP/AN93HC BL-BP/AN125HC BL-BP/AN155HC
BL-BP/AN185HC BL-BP/AN210HC BL-BP/AN255HC

IATA Compliance



see details

P5

Buddy System for Broadcasting Video Camera

- BL-T-BP/AN154 BL-T-BP/AN162 BL-T-BP/AN192

High Load

IATA Compliance



see details

P6

High Load Buddy System for Broadcasting Video Camera

- BL-V-BP/AN155 BL-V-BP/AN168 BL-V-BP/AN198



see details

P9

DV Battery Pack for Sony PMW-EX1/200/100/F3

- BL-U65N BL-U76N

see details

P10

DV Battery for Canon EOS300/500/XF305/300

- BL-BP975 BL-BP955



see details

P10

DV Battery for Panasonic AG-AC160/130

- BL-VBG51 BL-VBG38

see details

P19

Mount Plate for Double V-Lock Batteries

- BL-BTT-S



see details

P20

Quaternate D-Tap Cable

- BL-C-BTL

Broadcasting Video Camera Battery



- Modular assembling technique is used with specially-designed nickel sheet.
- Cell and PCM are all connected by using specially-designed nickel sheet for standard production.
- USB output is added for smart mobile phone and Apple products.



BL-BP95NC/AN95NC 95Wh

BL-BP95NC: V-Lock
BL-AN95NC: Gold mount



BL-BP130NC/AN130NC 130Wh

BL-BP130NC: V-Lock
BL-AN130NC: Gold mount



BL-BP160NC/AN160NC 160Wh

BL-BP160NC: V-Lock
BL-AN160NC: Gold mount



BL-BP95NE/AN95NE 95Wh

BL-BP95NE: V-Lock
BL-AN95NE: Gold mount



BL-BP130NE/AN130NE 130Wh

BL-BP130NE: V-Lock
BL-AN130NE: Gold mount



BL-BP160NE/AN160NE 160Wh

BL-BP160NE: V-Lock
BL-AN160NE: Gold mount



Max. Output 150W/12A

BL-BP190NC/AN190NC 190Wh

BL-BP190NC: V-Lock
BL-AN190NC: Gold mount



Max. Output 150W/12A

BL-BP230NC/AN230NC 230Wh

BL-BP230NC: V-Lock
BL-AN230NC: Gold mount



Max. Output 150W/12A

BL-BP190NE/AN190NE 190Wh

BL-BP190NE: V-Lock
BL-AN190NE: Gold mount



Max. Output 150W/12A

BL-BP230NE/AN230NE 230Wh

BL-BP230NE: V-Lock
BL-AN230NE: Gold mount

Model	Battery type	Voltage	Capacity	Max. Output	Typical run-time	Net weight	Dimension
BL-BP95NE	V-Lock	14.8V	6.6Ah/95Wh	79W/6.5A	162mins@35W	760g	172x102x41mm
BL-AN95NE	Gold mount	14.8V	6.6Ah/95Wh	79W/6.5A	162mins@35W	760g	172x102x51mm
BL-BP130NE	V-Lock	14.8V	8.8Ah/130Wh	79W/6.5A	222mins@35W	950g	172x102x47mm
BL-AN130NE	Gold mount	14.8V	8.8Ah/130Wh	79W/6.5A	222mins@35W	950g	172x102x57mm
BL-BP160NE	V-Lock	14.8V	11Ah/160Wh	79W/6.5A	274mins@35W	1120g	172x102x47mm
BL-AN160NE	Gold mount	14.8V	11Ah/160Wh	79W/6.5A	274mins@35W	1120g	172x102x57mm
BL-BP190NE	V-Lock	14.8V	13.2Ah/190Wh	150W/12A	115mins@100W	1120g	172x102x47mm
BL-AN190NE	Gold mount	14.8V	13.2Ah/190Wh	150W/12A	115mins@100W	1120g	172x102x57mm
BL-BP230NE	V-Lock	14.8V	15.6Ah/230Wh	150W/12A	138mins@100W	1320g	172x102x63mm
BL-AN230NE	Gold mount	14.8V	15.6Ah/230Wh	150W/12A	138mins@100W	1320g	172x102x73mm
BL-BP95NC	V-Lock	14.8V	6.6Ah/95Wh	79W/6.5A	162mins@35W	760g	172x102x41mm
BL-AN95NC	Gold mount	14.8V	6.6Ah/95Wh	79W/6.5A	162mins@35W	760g	172x102x51mm
BL-BP130NC	V-Lock	14.8V	8.8Ah/130Wh	79W/6.5A	222mins@35W	950g	172x102x47mm
BL-AN130NC	Gold mount	14.8V	8.8Ah/130Wh	79W/6.5A	222mins@35W	950g	172x102x57mm
BL-BP160NC	V-Lock	14.8V	11Ah/160Wh	79W/6.5A	274mins@35W	1120g	172x102x47mm
BL-AN160NC	Gold mount	14.8V	11Ah/160Wh	79W/6.5A	274mins@35W	1120g	172x102x57mm
BL-BP190NC	V-Lock	14.8V	13.2Ah/190Wh	150W/12A	115mins@100W	1120g	172x102x47mm
BL-AN190NC	Gold mount	14.8V	13.2Ah/190Wh	150W/12A	115mins@100W	1120g	172x102x57mm
BL-BP230NC	V-Lock	14.8V	15.6Ah/230Wh	150W/12A	138mins@100W	1320g	172x102x63mm
BL-AN230NC	Gold mount	14.8V	15.6Ah/230Wh	150W/12A	138mins@100W	1320g	172x102x73mm

High Load Battery for Broadcasting Video Camera



- High-power Li-Ion cell is used to support high-power constant output up to 180W and 15A.
- Modular assembling technique is used with specially-designed nickel sheet.
- Standard Power Tap connector for direct camera light supply.
- USB output is added for smart mobile phone and Apple products.



BL-BP93HC/AN93HC 93Wh

BL-BP93HC: V-Lock
BL-AN93HC: Gold mount



BL-BP125HC/AN125HC 125Wh

BL-BP125HC: V-Lock
BL-AN125HC: Gold mount



BL-BP155HC/AN155HC 155Wh

BL-BP155HC: V-Lock
BL-AN155HC: Gold mount



BL-BP93HE/AN93HE 93Wh

BL-BP93HE: V-Lock
BL-AN93HE: Gold mount



BL-BP125HE/AN125HE 125Wh

BL-BP125HE: V-Lock
BL-AN125HE: Gold mount



BL-BP155HE/AN155HE 155Wh

BL-BP155HE: V-Lock
BL-AN155HE: Gold mount

Model	Battery type	Voltage	Capacity	Typical run-time	Net weight	Dimension
BL-BP93HE	V-Lock	14.8V	6.3Ah/93Wh	31mins@180W	760g	172x102x41mm
BL-AN93HE	Gold mount	14.8V	6.3Ah/93Wh	31mins@180W	760g	172x102x51mm
BL-BP125HE	V-Lock	14.8V	8.5Ah/125Wh	42mins@180W	950g	172x102x47mm
BL-AN125HE	Gold mount	14.8V	8.5Ah/125Wh	42mins@180W	950g	172x102x57mm
BL-BP155HE	V-Lock	14.8V	10.5Ah/155Wh	52mins@180W	1120g	172x102x47mm
BL-AN155HE	Gold mount	14.8V	10.5Ah/155Wh	52mins@180W	1120g	172x102x57mm
BL-BP185HE	V-Lock	14.8V	62Ah/185Wh	62mins@180W	1130g	172x102x63mm
BL-AN185HE	Gold mount	14.8V	62Ah/185Wh	62mins@180W	1130g	172x102x73mm
BL-BP210HE	V-Lock	14.8V	14.5Ah/210Wh	70mins@180W	1120g	172x102x47mm
BL-AN210HE	Gold mount	14.8V	14.5Ah/210Wh	70mins@180W	1120g	172x102x57mm
BL-BP253HE	V-Lock	14.8V	17.1Ah/253Wh	85mins@180W	1320g	172x102x63mm
BL-AN253HE	Gold mount	14.8V	17.1Ah/253Wh	85mins@180W	1320g	172x102x73mm



BL-BP93HC/AN93HC 93Wh

BL-BP93HC: V-Lock
BL-AN93HC: Gold mount



BL-BP125HC/AN125HC 125Wh

BL-BP125HC: V-Lock
BL-AN125HC: Gold mount



BL-BP155HC/AN155HC 155Wh

BL-BP155HC: V-Lock
BL-AN155HC: Gold mount



BL-BP185HC/AN185HC 185Wh

BL-BP185HC: V-Lock
BL-AN185HC: Gold mount



BL-BP210HC/AN210HC 210Wh

BL-BP210HC: V-Lock
BL-AN210HC: Gold mount



BL-BP253HC/AN253HC 253Wh

BL-BP253HC: V-Lock
BL-AN253HC: Gold mount

Model	Battery type	Voltage	Capacity	Typical run-time	Net weight	Dimension
BL-BP93HC	V-Lock	14.8V	6.3Ah/93Wh	31mins@180W	760g	172x102x41mm
BL-AN93HC	Gold mount	14.8V	6.3Ah/93Wh	31mins@180W	760g	172x102x51mm
BL-BP125HC	V-Lock	14.8V	8.5Ah/125Wh	42mins@180W	950g	172x102x47mm
BL-AN125HC	Gold mount	14.8V	8.5Ah/125Wh	42mins@180W	950g	172x102x57mm
BL-BP155HC	V-Lock	14.8V	10.5Ah/155Wh	52mins@180W	1120g	172x102x47mm
BL-AN155HC	Gold mount	14.8V	10.5Ah/155Wh	52mins@180W	1120g	172x102x57mm
BL-BP185HC	V-Lock	14.8V	62Ah/185Wh	62mins@180W	1130g	172x102x63mm
BL-AN185HC	Gold mount	14.8V	62Ah/185Wh	62mins@180W	1130g	172x102x73mm
BL-BP210HC	V-Lock	14.8V	14.5Ah/210Wh	70mins@180W	1120g	172x102x47mm
BL-AN210HC	Gold mount	14.8V	14.5Ah/210Wh	70mins@180W	1120g	172x102x57mm
BL-BP253HC	V-Lock	14.8V	17.1Ah/253Wh	85mins@180W	1320g	172x102x63mm
BL-AN253HC	Gold mount	14.8V	17.1Ah/253Wh	85mins@180W	1320g	172x102x73mm

Buddy System for Broadcasting Video Camera

- Buddy system could be divided into two parts to meet the regulations of International Air Transport Association.
- Built-in 5-level LED power indicator display.
- Standard Power Tap connector that is able to directly supply ultralight camera light.
- USB output is added for smart mobile phone and Apple products.



BL-T-BP154 154Wh

- V-Lock
- For RED Camera
- Remaining power in percentage can be read in camera viewfinder



BL-T-BP192/AN192 192Wh

BL-T-BP192: V-Lock
BL-T-AN192: Gold mount

BL-T-BP162: V-Lock
BL-T-AN162: Gold mount

Model	Battery type	Voltage	Capacity	Max. Output	Typical run-time	Net weight	Dimension
BL-T-BP154	V-Lock	14.8V	Double 5.2Ah, 77Wh	79W/6.5A	264mins@35W	1120g	170x100x57mm
BL-T-BP162	V-Lock	14.8V	Double 5.5Ah, 81Wh	79W/6.5A	278mins@35W	1300g	170x100x57mm
BL-T-AN162	Gold mount	14.8V	Double 5.5Ah, 81Wh	79W/6.5A	278mins@35W	1300g	170x100x53mm
BL-T-BP192	V-Lock	14.8V	Double 6.5Ah, 96Wh	150W/12A	115mins@100W	1300g	170x100x57mm
BL-T-AN192	Gold mount	14.8V	Double 6.5Ah, 96Wh	150W/12A	115mins@100W	1300g	170x100x53mm

Buddy System for Broadcasting Video Camera

- Buddy system could be divided into two parts to meet the regulations of International Air Transport Association.
- High-power Li-ion cell is used to support high-power constant output upto 180W and 15A.
- Built-in 5-level LED power indicator display.
- Standard Power Tap connector that is able to directly supply ultralight camera light.
- USB output is added for smart mobile phone and Apple products.



BL-V-BP168 168Wh

- V-Lock
- For RED Camera
- Remaining power in percentage can be read in camera viewfinder



BL-V-BP198/AN198 198Wh

BL-V-BP198: V-Lock
BL-V-AN198: Gold mount

BL-V-BP155: V-Lock
BL-V-AN155: Gold mount

Model	Battery type	Voltage	Capacity	Max. Output	Typical run-time	Net weight	Dimension
BL-V-BP168	V-Lock	14.8V	Double 5.7Ah, 84Wh	180W/15A	56mins@180W	1120g	170x100x57mm
BL-V-BP155	V-Lock	14.8V	Double 5.25Ah, 77.5Wh	180W/15A	52mins@180W	1300g	170x100x57mm
BL-V-BP155	Gold mount	14.8V	Double 5.25Ah, 77.5Wh	180W/15A	52mins@180W	1300g	170x100x53mm
BL-V-AN198	V-Lock	14.4V	Double 6.9Ah, 99Wh	180W/15A	66mins@100W	1300g	170x100x57mm
BL-V-AN198	Gold mount	14.4V	Double 6.9Ah, 99Wh	180W/15A	66mins@100W	1300g	170x100x53mm

Broadcasting Video Camera Battery

- Built-in 4-level LED power indicator.
- Standard Power Tap connector that is able to directly supply ultralight camera light.
- Built-in battery management system for multiple protect functions of over temperature, over current, over voltage, short circuit, etc.



BL-NP65 65Wh

BL-NP65: NP type



BL-BP65/AN65 65Wh

BL-BP65: V-Lock
BL-AN65: Gold mount



BL-BP160/AN160 160Wh

BL-BP160: V-Lock
BL-AN160: Gold mount



BL-BP190/AN190 190Wh

BL-BP190: V-Lock
BL-AN190: Gold mount



BL-BP230/AN230 230Wh

BL-BP230: V-Lock
BL-AN230: Gold mount



BL-BP95/AN95 95Wh

BL-BP95: V-Lock
BL-AN95: Gold mount



BL-BP130/AN130 130Wh

BL-BP130: V-Lock
BL-AN130: Gold mount



BL-BP230-12A/AN230-12A 230Wh Max. output: 12A

BL-BP230: V-Lock
BL-AN230: Gold mount

Model	Battery type	Voltage	Capacity	Typical run-time	Net weight	Dimension
BL-NP65	NP	14.8V	4.4Ah/65Wh	130mins@30W	450g	184x71x25mm
BL-BP65	V-Lock	14.8V	4.4Ah/65Wh	130mins@30W	530g	153x102x36mm
BL-AN65	Gold mount	14.8V	4.4Ah/65Wh	130mins@30W	530g	153x102x41mm
BL-BP95	V-Lock	14.8V	6.6Ah/95Wh	190mins@30W	700g	153x102x43mm
BL-AN95	Gold mount	14.8V	6.6Ah/95Wh	190mins@30W	700g	153x102x48mm
BL-BP130	V-Lock	14.8V	8.8Ah/130Wh	260mins@30W	910g	153x102x53mm
BL-AN130	Gold mount	14.8V	8.8Ah/130Wh	260mins@30W	910g	153x102x58mm
BL-BP160	V-Lock	14.8V	11Ah/160Wh	320mins@30W	1100g	153x102x53mm
BL-AN160	Gold mount	14.8V	11Ah/160Wh	320mins@30W	1100g	153x102x58mm
BL-BP190	V-Lock	14.8V	13.2Ah/190Wh	380mins@30W	1250g	153x102x63mm
BL-AN190	Gold mount	14.8V	13.2Ah/190Wh	380mins@30W	1250g	153x102x68mm
BL-BP230	V-Lock	14.8V	15.6Ah/230Wh	460mins@30W	1350g	153x102x63mm
BL-AN230	Gold mount	14.8V	15.6Ah/230Wh	460mins@30W	1350g	153x102x68mm
BL-BP230-12A	V-Lock	14.8V	15.6Ah/230Wh	95mins@145W	1350g	153x102x68mm
BL-AN230-12A	Gold mount	14.8V	15.6Ah/230Wh	95mins@145W	1350g	153x102x68mm

DV Battery Pack for Sony

- Built-in 4-level LED power indicator.
- Built-in battery management system for multiple protect functions of over temperature, over current, over voltage, short circuit, etc.
- Charge with specified Beillen charger: BL-BCY-U/BL-T1A-B.



DV Battery Pack for Sony

- Built-in battery management system for multiple protect functions of over temperature, over current, over voltage, short circuit, etc.
- Charge with specified Beillen charger: BL-BCR-S/BL-BCX-S/BL-BCY-S.



DV Battery Pack for JVC

- Built-in 4-level power indicator.
- Built-in battery management system for multiple protection of over temperature, over current, over voltage, short circuit, etc.
- Charge with specified Beillen charger: BL-BCR-J/BL-BCX-J/BL-BCY-J.

BL-V488 65Wh



DV Battery Pack for Panasonic

- Built-in 4-level LED power indicator.
- Built-in battery management system for multiple protect functions of over temperature, over current, over voltage, short circuit, etc.
- BL-VBG51/BL-VBG38: charge with specified Beillen charger: BL-BCY-V.
- BL-D88/BL-D66: charge with specified Beillen charger: BL-BCR-P/BL-BCX-P/BL-BCY-P.



DV Battery Pack for Canon

- Built-in battery management system for multiple protection of over temperature, over current, over voltage, short circuit, etc.
- Charge with specified Beillen charger: BL-BCR-C/BL-BCX-C/BL-BCY-C.



Model	Capacity	Voltage	Typical run-time	Net weight	Dimension	Applicable to
BL-U65N	4.4Ah/65Wh	14.8V	229mins@17W	380g	93x70x41.6mm	Sony PMW EX1R, PMW-200, PMW-100, PMW-F3,
BL-U76N	5.2Ah/76Wh	14.8V	268mins@17W	383g	93x70x41.6mm	
BL-U95	6.6Ah/95Wh	14.8V	475mins@12W	650g	131x70x42mm	
BL-F770	4.4Ah/32Wh	7.4V	160mins@12W	200g	71x39x38mm	Sony DCR-VX2100, DSR-PD170, HDR-FX1, HVR-Z1, HVR-V1
BL-F970	6.6Ah/49Wh	7.4V	245mins@12W	300g	71x60x38mm	
BL-F1170M	8.8Ah/65Wh	7.4V	325mins@12W	406g	90x67x38mm	
BL-V488	8.8Ah/65Wh	7.4V	325mins@12W	396g	91x67x38mm	JVC GY-HD101EC, BR-HD50EC, DR-HD100EC
BL-VBG51	6.9Ah/51Wh	7.4V	180mins@17W	270g	81.6x65.2x36mm	Panasonic AG-AC160, AG-AC130, AG-AF101, AG-HMC41, AG-HMC81, G-HM151
BL-VBG38	5.2Ah/38Wh	7.4V	134mins@17W	212g	81.6x65.2x36mm	
BL-D88	8.8Ah/65Wh	7.4V	325mins@12W	385g	93x67x36mm	Panasonic AG-DVC30, AG-DVC60, AG-DVX100, AG-HVX200, AJ-PCS060, AG-HPG10
BL-D66	6.6Ah/49Wh	7.4V	245mins@12W	300g	75x56x38mm	
BL-BP988	8.8Ah/65Wh	7.4V	325mins@12W	404g	82x67x38mm	Canon XL1S, SM1, XM2, XL2
BL-BP975	6.6Ah/49Wh	7.4V	245mins@17W	270g	58x70.6x38.2mm	Canon XF305, XF300, XF105, XF100, XL-H1A, XH-G1, XH-A1, XL2/XM2, EOS 100, 300, 500
BL-BP955	4.4Ah/32Wh	7.4V	160mins@17W	113g	40x70.6x38.2mm	

Charger for Broadcasting Video Camera Battery

- Special for Beillen Li-Ion battery.
- Constant-current and constant-voltage charging modes are used to ensure the battery can be charged in optimum state.
- Built-in DC adapter with 16.7V and 4.5A output.



- Special for Beillen Li-Ion battery.
- Constant-current and constant-voltage charging modes are used to ensure the battery can be charged in optimum state.
- Built-in DC adapter with 15V and 4.0A output.



BLB-BP2E
2-Channel Portable Li-Ion Battery Charger

AC input	100~240V 50~60Hz
Output charging terminals 1 & 2	16.8V 2.5A/5.0A
DC output	16.7V 4.5A
Net weight	990g
Storage environment	-20℃ ~ +55℃ 45% ~ 75%RH (<1 year)
Working environment	-10℃ ~ +45℃ <85%RH
Applicable to	V-Lock Li-Ion batteries



BLB-BP4E
4-Channel Portable Li-Ion Battery Charger

AC input	100~240V 50~60Hz
Output charging terminals 1 to 4	16.8V 2.5A
DC output	15V 4.0A
Net weight	2900g
Storage environment	-20℃ ~ +55℃ 45% ~ 75%RH (<1 year)
Working environment	-10℃ ~ +45℃ <85%RH
Applicable to	V-Lock Li-Ion batteries



BLB-AN2E
2-Channel Portable Li-Ion Battery Charger

AC input	100~240V 50~60Hz
Output charging terminals 1 & 2	16.8V 2.5A/5.0A
DC output	16.7V 4.5A
Net weight	1000g
Storage environment	-20℃ ~ +55℃ 45% ~ 75%RH (<1 year)
Working environment	-10℃ ~ +45℃ <85%RH
Applicable to	Gold mount Li-Ion batteries



BLB-AN4E
4-Channel Portable Li-Ion Battery Charger

AC input	100~240V 50~60Hz
Output charging terminals 1 to 4	16.8V 2.5A
DC output	15V 4.0A
Net weight	2930g
Storage environment	-20℃ ~ +55℃ 45% ~ 75%RH (<1 year)
Working environment	-10℃ ~ +45℃ <85%RH
Applicable to	Gold mount Li-Ion batteries



BLB-NP2B
2-Channel Desktop Charger for NP Type Battery

- Special for Beillen NP type Li-Ion battery.
- Charge and DC adapter functions can be used simultaneously.
- Constant-current and constant-voltage charging modes are used to ensure the battery can be charged in optimum state.
- Applicable to NP type Li-Ion batteries.

Model	BLB-NP2B
AC input	100~240V 50~60Hz
Output charging terminals 1 & 2	16.8V 2.5A
DC output	15V 4.0A
Net weight	2000g
Storage environment	-20℃ ~ +55℃ 45% ~ 75%RH (1 year)
Working environment	0℃ ~ +45℃ <85%RH



BLB-T1A-B
Portable Li-Ion Battery Charger

- Special for Beillen Li-Ion battery.
- Constant-current and constant-voltage charging modes to are used ensure the battery can be charged in optimum state.
- Charge by Power Tap connector.
- Applicable to batteries with Power Tap connector.

Model	BLB-T1A-B
AC input	100~240V 50~60Hz
DC output	16.8V 2.0A
Net weight	480g
Storage environment	-20℃ ~ +55℃ 45% ~ 75%RH (1 year)
Working environment	0℃ ~ +45℃ <85%RH



BLB-NP4BA
4-Channel Desktop Charger for NP Type Battery

- Special for Beillen NP type Li-ion battery.
- Charge and DC adapter functions can be used simultaneously.
- Constant-current and constant-voltage charging modes are used to ensure the battery can be charged in optimum state.
- Applicable to NP type Li-Ion batteries.

Model	BLB-NP4BA
AC input	100~240V 50~60Hz
Output charging terminals 1 & 4	16.8V 2.5A
DC output	15V 4.0A
Net weight	2700g
Storage environment	-20℃ ~ +55℃ 45% ~ 75%RH (1 year)
Working environment	0℃ ~ +45℃ <85%RH



BLD-P1A
Portable Power Adapter

- Most advanced switching power supply design for compactness, lightweight and high-efficiency.
- Super filter technique for safety and silence.
- Prover DC15V power supply for all kinds of professional video cameras.

Model	BLD-P1A
AC input	100~240V 50~60Hz
DC output	15V 4.0A
Net weight	500g
Storage environment	-20℃ ~ +55℃ 45% ~ 75%RH (1 year)
Working environment	0℃ ~ +45℃ <85%RH



BLB-T1A
Portable Li-Ion Battery Charger

- Special for Beillen Li-Ion battery.
- Constant-current and constant-voltage charging modes to are used ensure the battery can be charged in optimum state.
- Charge by DC connector.
- Applicable to batteries with DC connector.

Model	BLB-T1A
AC input	100~240V 50~60Hz
DC output	16.8V 2.0A
Net weight	480g
Storage environment	-20℃ ~ +55℃ 45% ~ 75%RH (1 year)
Working environment	0℃ ~ +45℃ <85%RH



BL-BCZ
Vehicle Charger for Li-Ion Battery

- Applicable to:Beillen 14.8V professional video camera battery.
- Charge and adapter functions should be used separately.

Model	BL-BCZ
DC input	10~26V
Adapter output	12V 2.0A
Charger output	16.8V 2.0A
Net weight	470g
Storage environment	-20℃ ~ +55℃ 45% ~ 75%RH (1 year)
Working environment	0℃ ~ +45℃ <85%RH

1-Channel Charger for DV Battery



BL-BCR-S Charger



BL-BCR-P Charger



Adapter



BL-BCR-C Charger



BL-BCR-J Charger

BL-BCR-S

Applicable to: BL-F770/BL-F970/BL-F1170M/NP-F970/
NP-F960/NP-F770/NP-F750/NP-F570/NP-F550

BL-BCR-P

Applicable to: BL-D66/BL-D88/CGR D320/D54

BL-BCR-C

Applicable to: BL-BP975/BL-BP955/BL-BP988/BP945/
BP915/BP975/BP955

BL-BCR-J

Applicable to: BL-V488/BN-V428

Model	BL-BCR-S	BL-BCR-P	BL-BCR-C	BL-BCR-J
AC input	100~240V 50~60Hz			
DC output	8.4V 17W 2.0A			
Net weight	138g			
Dimension	105x58x15mm (charger) 65x55x35mm (adapter)			
Storage environment	-20℃ ~ +55℃ 45% ~ 75%RH (1 year)			
Working environment	0℃ ~ +45℃ <85%RH			

2-Channel Charger for DV Battery



BL-BCX-S/BL-BCX-P/BL-BCX-C/BL-BCX-J



BL-BCY-U

Applicable to: BL-U65N/BL-U76N/BL-U95/BP-U60

BL-BCX-S/BL-BCY-S

Applicable to: BL-F770/BL-F970/BL-F1170M/NP-F970/
NP-F960/NP-F770/NP-F750/NP-F570/NP-F550

BL-BCX-P/BL-BCY-P

Applicable to: BL-D66/BL-D88/CGR D320/D54

BL-BCX-C/BL-BCY-C

Applicable to: BL-BP975/BL-BP955/BL-BP988/BP945/
BP915/BP975/BP955

BL-BCX-J/BL-BCY-J

Applicable to: BL-V488/BN-V428

2-Channel Quick Charger for DV Battery



BL-BCY-S/BL-BCY-P/BL-BCY-C/BL-BCY-J



BL-BCY-V

Applicable to: BL-VBG51/BL-VBG38/VN-VBG6

Model	AC input	Output charging terminals 1 & 2	DC output	Net weight	Dimension	Environment
BL-BCX-S	100~240V 50~60Hz	8.4V 1.5A	8.0V 3.0A	410g	170x110x50mm	Storage : -20℃ ~ +55℃ 45% ~ 75%RH (1 year) Working: 0℃ ~ +45℃ <85%RH
BL-BCX-P	100~240V 50~60Hz	8.4V 1.5A	8.0V 3.0A	410g	170x110x50mm	
BL-BCX-C	100~240V 50~60Hz	8.4V 1.5A	8.0V 3.0A	410g	170x110x50mm	
BL-BCX-J	100~240V 50~60Hz	8.4V 1.5A	8.0V 3.0A	410g	170x110x50mm	
BL-BCY-U	100~240V 50~60Hz	16.8V 1.8A	/	420g	170x110x50mm	
BL-BCY-S	100~240V 50~60Hz	8.4V 3.2A	8.0V 3.2A	420g	170x110x50mm	
BL-BCY-P	100~240V 50~60Hz	8.4V 3.2A	8.0V 3.2A	420g	170x110x50mm	
BL-BCY-C	100~240V 50~60Hz	8.4V 3.2A	8.0V 3.2A	420g	170x110x50mm	
BL-BCY-J	100~240V 50~60Hz	8.4V 3.2A	8.0V 3.2A	420g	170x110x50mm	
BL-BCY-V	100~240V 50~60Hz	8.4V 3.2A	8.0V 3.2A	420g	170x110x50mm	

High Power Li-Ion Battery

- Built-in 4-level LED power indicator.
- Standard XLR connector/ POWER CON connector.
- Built-in battery management system for mutple protect functions of over temperature, over current, over voltage, short circuit, etc.
- Charge with specified Beillen charger.
- Applicable to high power lighting, HD camera, film camera and laptop video editor, etc.



BL-BLP780 780Wh

Model	Capacity	Voltage	Typical run-time	Net weight	Dimension
BL-BLP780	780Wh	30V/15V	230mins@200W	9500g	300x270x115mm
BL-BLP520	520Wh	30V/15V	150mins@200W	4500g	265x210x85mm
BL-BLT420	420Wh	24V/12V	125mins@200W	3800g	265x210x85mm

XLR connector
Max: 15A

Power CON connector
Max: 30A



BL-BLP520 520Wh

BL-BLT420 420Wh

High Power Li-Ion Battery Charger



BL-T1B

Applicable to BL-BLP series high power Li-Ion batteries

AC input	100~240V 50~60Hz
DC output	16.8V 7A
Net weight	1000g
Storage environment	-10℃ ~ +45℃ 45% ~ 75%RH (<1 year)
Working environment	0℃ ~ +45℃ <85%RH



BL-T1C

Applicable to BL-BLT series high power Li-Ion batteries.

AC input	100~240V 50~60Hz
DC output	12.6V 7A
Net weight	1000g
Storage environment	-10℃ ~ +45℃ 45% ~ 75%RH (<1 year)
Working environment	0℃ ~ +45℃ <85%RH

Mount Plate



BL-BTT-S



BL-BTK-S



BL-BTB-A




BL-HD100BP



BL-HD100AN



BL-BTE



BL-BTH-B



BL-BTH-A



BL-BTJ

Cable



BL-C-BM



BL-C-BF



BL-C-BMF



BL-C-BX



BL-C-BTY



BL-C-BT0



BL-C-BTP



BL-C-BTM



BL-C-BTL



Global Presence

