

HPC-A30-MK2

CLOSED-BACK  
STUDIO MONITOR  
HEADPHONES



PRODUCT  
MANUAL



POLSEN®

## PRECAUTIONS

- Keep this unit away from water and any flammable gases or liquids.
- Clean the unit with only a soft, dry cloth.
- Make sure that this product is intact and that there are no missing parts.
- Be mindful of your surrounding environment when using this product. Do not use this product while driving an automobile, operating machinery, or performing other tasks that require your undivided attention.
- All images are for illustrative purposes only.

### Protect Your Hearing

Exposure to high sound pressure levels may cause permanent hearing loss. Avoid listening at high volumes for extended periods.


Symptoms of noise-induced hearing loss may include persistent ringing, pain, itching, or inflammation of the ears, and difficulty understanding speech.

For more information visit:

[https://www.cdc.gov/nceh/hearing\\_loss/](https://www.cdc.gov/nceh/hearing_loss/)

## THANK YOU FOR CHOOSING POLSEN.


Polsen's HPC-A30-MK2 headphones deliver rich sound whether you're listening to music on a mobile device or monitoring a podcast or audio production on your computer. The headphones are also ideal for DJs thanks to the swiveling earcups that let you monitor your audio while keeping one ear free. The 10-foot cable gives you the freedom to move around, so you're not tethered to your computer or mixer while you're working. The over-the-ear design isolates the sound and prevents leakage for optimum listening conditions in a loud environment.



# OVERVIEW



Folds up for  
convenient storage  
and travel



Earcup swivels  
for one-ear  
monitoring



Earcup  
rotates 90° for  
on-the-shoulder monitoring

## SPECIFICATIONS

**Type** Circumaural, closed back

**Frequency Response** 20 Hz to 20 kHz

**Impedance** 32  $\Omega$

**Sensitivity** 102 dB

**Maximum Power Handling** 300 mW

**Rated Power** 15 mW

**Magnet Type** Neodymium

**Driver Diameter** 2 in. (50 mm)

**Total Harmonic Distortion** <0.25% at 1 kHz / 1 V

**Cable Diameter** 0.1 in. (3 mm)

**Cable Length** 10 ft. (3 m)

**Weight** 10.2 oz. (290 g)

## ONE-YEAR LIMITED WARRANTY

This Polsen product is warranted to the original purchaser to be free from defects in materials and workmanship under normal consumer use for a period of one (1) year from the original purchase date or thirty (30) days after replacement, whichever occurs later. The warranty provider's responsibility with respect to this limited warranty shall be limited solely to repair or replacement, at the provider's discretion, of any product that fails during normal use of this product in its intended manner and in its intended environment. Inoperability of the product or part(s) shall be determined by the warranty provider. If the product has been discontinued, the warranty provider reserves the right to replace it with a model of equivalent quality and function.

This warranty does not cover damage or defect caused by misuse, neglect, accident, alteration, abuse, improper installation or maintenance. EXCEPT AS PROVIDED HEREIN, THE WARRANTY PROVIDER MAKES NEITHER ANY EXPRESS WARRANTIES NOR ANY IMPLIED WARRANTIES, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. This warranty provides you with specific legal rights, and you may also have additional rights that vary from state to state.

To obtain warranty coverage, contact the Polsen Customer Service Department to obtain a return merchandise authorization ("RMA") number, and return the defective product to Polsen along with the RMA number and proof of purchase. Shipment of the defective product is at the purchaser's own risk and expense.

For more information or to arrange service, visit [www.polsenaudio.com](http://www.polsenaudio.com) or call Customer Service at 212-594-2353.

Product warranty provided by the Gradus Group.  
[www.gradusgroup.com](http://www.gradusgroup.com)

Polsen is a registered trademark of the Gradus Group.  
© 2019 Gradus Group LLC. All Rights Reserved.

